

1/17




Fig. 1

2/17




Fig. 2




Fig. 3

4/17




Fig. 4




Fig. 5




Fig. 6

6/17




Fig. 7

7/17




Fig. 8

8/17

Table 1

RAB service attribute	RAB service attribute value		Comments
Traffic Class	Conversational		
RAB Asymmetry Indicator	Symmetric, bidirectional		Symmetric RABs are used for uplink and downlink
Maximum bit rate	12,65 kbit/s in configurations 0 and 1 15,85 kbit/s in configurations 2 and 3 23,85 kbit/s in configurations 4 and 5		This value depends on the highest mode rate in the RFCS (note 2)
Guaranteed bit rate	6,60 kbit/s		One of the values chosen, depending on the lowest rate controllable SDU format (note 2)
Delivery Order	Yes		(note 1)
Maximum SDU size	253 in configurations 0 and 1 317 in configurations 2 and 3 477 in configurations 4 and 5		Maximum size of payload field in Lu UP, according to the highest mode rate in the RFCS (note 2)
Traffic Handling Priority	Not applicable		Parameter not applicable for the conversational traffic class (note 1)
Source statistics descriptor	Speech		(note 1)
SDU Parameters	RAB subflow 1 (Class A bits)	RAB subflow 2 (Class B bits)	The number of SDU, their number of RAB subflow is subject to operator tuning (note 3)

Fig. 9 (continued on page 9/17)

9/17

SDU error ratio	$7 \cdot 10^{-3}$	-	(note 3)
Residual bit error ratio	$10^{-6}$	$10^{-3}$	(note 3 - applicable for every subflow)
Delivery of erroneous SDUs	Yes	-	Class A bits are delivered with error indication; Class B bits are delivered without any error indication
SDU format information 1-5			(note 4)
sub-flow SDU size 1-5	(note 5)	(note 5)	

NOTE 1: These parameters apply to all UMTS speech codec types.

NOTE 2: The guaranteed bit rate depends on the periodicity and the lowest rate controllable SDU size. All UMTS\_AMR-WB configurations as defined in TS 26.103 contain the 6,60 kbps codec mode as lowest and therefore "guaranteed bit rate". The "maximum bit rate" and the "maximum SDU size" depend on the selected UMTS\_AMR-WB configuration.

NOTE 3: These parameters are subject to operator tuning.

NOTE 4: SDU format information has to be specified for each AMR-WBcore frame type (i.e. with speech bits and comfort noise bits) included in the RFCS as defined in [2].

NOTE 5: The subflow SDU size corresponding to an AMR-WBcore frame type indicates the number of bits in the class A, class B fields as specified in Table 2 (see Fig.10)

Fig. 9 (continued from page 8/17)

10/17

Table 2:

Frame Type Index	No of Class A Bits per frame	No of Class B Bits per frame	No of Class C Bits per frame	Total No. of Bits per frame
1	64	113	0	198
2	72	181	0	274
3	72	213	0	306
4	72	245	0	338
5	72	293	0	386

Fig. 10

11/17

Table 3

UMTS_AMR-WB	RAB sub-flows		Total number of bits per RAB sub-flow combination (Mandatory)	Source rate
RFCI	RAB sub-flow 1 (Optional)	RAB sub-flow 2 (Optional)		
Example 1				
1	40	0	40	AMR-WB SID
2	54	78	132	AMR-WB 6.6 kbps
3	64	113	177	AMR-WB 8.85 kbps
4	72	181	253	AMR-WB 12.65 kbps
Example 2				
1	40	0	40	AMR-WB SID
2	54	78	132	AMR-WB 6.6 kbps
3	64	113	177	AMR-WB 8.85 kbps
4	72	181	253	AMR-WB 12.65 kbps
5	73	244	317	AMR-WB 15.85 kbps
Example 3				
1	40	0	40	AMR-WB SID
2	54	78	132	AMR-WB 6.6 kbps
3	64	113	177	AMR-WB 8.85 kbps
4	72	181	253	AMR-WB 12.65 kbps
5	74	403	477	AMR-WB 23.85 kbps

Fig. 11

12/17

8	7	6	5	4	3	2	1	Octet 1
Quality of service IEI								Octet 2
Length of quality of service IE								Octet 3
0 0 spare			Delay class				Reliability class	Octet 4
	Peak throughput			0 spare			Precedence class	Octet 5
0 0 0 spare							Mean throughput	Octet 6
Traffic Class			Delivery order				Delivery of erroneous SDU	Octet 7
							Maximum SDU size	Octet 8
							Maximum bit rate for uplink	Octet 9
							Maximum bit rate for downlink	Octet 10
Residual BER							SDU error ratio	Octet 11
			Transfer delay				Traffic Handling priority	Octet 12
							Guaranteed bit rate for uplink	Octet 13
							Guaranteed bit rate for downlink	

Fig. 12

13/17

8	7	6	5	4	3	2	1	Octet 1
Quality of service IEI								Octet 2
Length of quality of service IE								Octet 3
0 0 spare		Delay class		Reliability class		Precedence class		Octet 4
Peak throughput		0 spare		Mean throughput				Octet 5
Optional QoS Indication Bits		Delivery order		Delivery of erroneous SDU				Octet 6
Maximum SDU size								Octet 7
Maximum bit rate for uplink								Octet 8
Maximum bit rate for downlink								Octet 9
Residual BER		SDU error ratio		Traffic Handling priority				Octet 10
Transfer delay								Octet 11
Guaranteed bit rate for uplink								Octet 12
Guaranteed bit rate for downlink								Octet 13
QoS optional field 1								Octet 14
QoS optional field 2								Octet 22
								Octet 23
								Octet 31

Fig. 13




Fig. 14

15/17




Fig. 15




Fig. 16

17/17




Fig. 17